

DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA)

BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

R. C. Aluminum Industries, Inc. 2805 NW 75th Ave Miami, FL 33122

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA-Product Control Section to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "HP-3070" Aluminum Window Wall System - L.M.J.

APPROVAL DOCUMENT: Drawing No. W03-115, titled "HP-3070 Alum. Window Wall System (L.M.I.)", sheets 1 through 7 of 7 (including Sheet 2.1), prepared by AL-Farooq Corporation, with latest revised "J" dated 03/08/12, signed and sealed by Javad Ahmad, P. E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and Expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, series and following statement: "Miami-Dade County Product Control Approved" unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/ or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 10-0525.04 and consists of this page 1, evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Jaime D. Gascon, P. E.

MIAMI-DADE COUNTY
APPROVED

J.GASLON

NOA No. 12-0330.14 Expiration Date: March 15, 2014 Approval Date: June 21, 2012

MIAMI-DADE COUNTY, FLORIDA
PRODUCT CONTROL SECTION

T (786) 315-2590 F (786) 315-2599

11805 SW 26 Street, Room 208

Miami, Florida 33175-2474

www.miamidade.gov/pera/

Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

1. Manufacturer's die drawings and sections.

(Submitted under previous NOA's No.'s 03-1224.03, 08-1217.01 and 10-0525.04)

2. Drawing No. W03-115, titled "HP-3070 Alum. Window Wall System (L.M.I.)", sheets 1 through 7 of 7 (including Sheet 2.1), prepared by AL-Farooq Corporation, with latest revised "J" dated 03/08/12, signed and sealed by Javad Ahmad, P. E.

B. TESTS

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202–94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Safety Glazing Performance Test, per FBC, ANSI Z 97.1–04 Class A and CPSC 16 CFR 1201, Category II

along with marked-up drawings and installation diagram of an aluminum window wall system, prepared by the following testing laboratories:

- a) Fenestration Testing Laboratory, Inc., Test Reports No.'s:
 - I. FTL-6123, dated 03/17/10, signed and sealed by Jorge A. Causo, P. E. (See above items B.1.1 thru B.1.6).

(Submitted under previous NOA No. 10-0525.04)

II. FTL-5934, dated 04/22/09, FTL-5935, dated 04/22/09 and FTL-5319, dated 07/05/07, all signed and sealed by Carlos S. Rionda, P. E. (See above item B.1.6).

(Submitted under previous NOA's No.'s 10-0525.04 and 08-1217.01)

- III. FTL-3956, dated 11/14/03 and FTL-3182, dated 12/12/01, both signed and sealed by Edmundo Largaespada, P. E. (See above items B.1.1 thru B.1.5). (Submitted under previous NOA No. 03-1224.03)
- b) Hurricane Engineering and Testing, Inc., Test Reports No.'s:
 - I. HETI-02-1265, dated 2/27/03 and HETI-03-1781, dated 11/15/02, both signed and sealed by Rafael E. Droz-Seda, P. E. (See above items B.1.1 through B.1.3).

(Submitted under previous NOA No. 03-1224.03)

C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC, prepared by AL-Farooq Corporation, dated 04/19/10, signed and sealed by Javad Ahmad, P. E.

(Submitted under previous NOA No. 10-0525.04)

2. Glazing complies with ASTM E 1300-04

Jaime D. Gascon, P. E.

Product Control Section Supervisor

NOA No. 12-0330.14

Expiration Date: March 15, 2014 Approval Date: June 21, 2012

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. QUALITY ASSURANCE

1. Miami-Dade Department of Permitting, Environment, and Regulatory Affairs (PERA).

E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. 11-0624.02 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont Sentry Glass® Interlayer" dated 05/26/2010, expiring on 01/14/17.
- 2. Notice of Acceptance No. 08-0520.08 issued to Solutia, Inc. for their "Vanceva Composite Glass Interlayer" approved on 07/17/08, expiring on 12/11/13.

F. STATEMENTS

- 1. Statement letter of no financial interest, conformance and compliance with the FBC-2010, dated 03/05/12, signed and sealed by Javad Ahmad, P. E.
- 2. Laboratory compliance letters prepared by Fenestration Testing Laboratory, Inc., for the following Test Reports No.'s:
 - I. FTL-6123, dated 03/17/10, signed and sealed by Jorge A. Causo, P. E. (Submitted under previous NOA No. 10-0525.04)
 - II. FTL-5935 dated 04/22/09, FTL-5934 dated 04/22/09 and FTL-5319 dated 07/05/07, all signed and sealed by Carlos S. Rionda, P. E.

(Submitted under previous NOA's No.'s 10-0525.04 and 08-1217.01)

III. FTL-3956 dated 11/14/03 and FTL-3182 dated 12/12/01, both signed and sealed by Edmundo Largaespada, P. E.

(Submitted under previous NOA No. 03-1224.03)

- 3. Laboratory compliance letters prepared by Hurricane Engineering and Testing, Inc., for the following Test Reports No.'s:
 - I. HETI-02-1265 dated 2/27/03 and HETI-03-1781 dated 11/15/02, both signed and sealed by Rafael E. Droz-Seda, P. E.

(Submitted under previous NOA No. 03-1224.03)

- 4. Proposal of Safety Glazing Performance Test, per ANSI Z 97.1–04 Class A and CPSC 16 CFR 1201, Category II issued by Product Control, dated 10/24/06, signed by Jaime D. Gascon, P. E. (Submitted under previous NOA No. 08–1217.01)
- 5. Proposal No. 04–0199 issued by Product Control, dated 05/14/04, signed by Manuel Perez, P. E. (Submitted under NOA No. 05–0815.02)

G. OTHERS

Same and


1. Notice of Acceptance No. 10-0525.04, issued to R. C. Aluminum Industries, Inc., for their Series "HP-3070 Aluminum Window Wall System - L.M.I.", approved on 09/08/10 and expiring on 03/15/14.

Jaime D. Gascon, P. E.

Product Control Section Supervisor

NOA No. 12-0330.14 Expiration Date: March 15, 2014

Approval Date: June 21, 2012



TYPICAL ELEVATIONS

HP3070 ALUM. WINDOW WALL SYSTEM (L.M.I.)

THIS SYSTEM IS RATED FOR LARGE & SMALL MISSILE IMPACT. SHUTTERS ARE NOT REQUIRED.

THIS SYSTEM MAY BE USED IN CONJUNCTION WITH MIAMI-DADE COUNTY APPR'D LARGE MISSILE IMPACT RESISTANT DOORS. FOR CONNECTION DETAILS TO MULLION SEE SEPARATE DOOR NOA.

CODE REQUIREMENTS FOR SAFEGUARDS MUST BE OBSERVED.

THIS PRODUCT HAS BEEN DESIGNED AND TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE INCLUDING HIGH VELOCITY HURRICANE ZONE (HVHZ).

ANCHORS SHALL BE AS LISTED, SPACED AS SHOWN ON DETAILS, ANCHORS EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO.

ANCHORING OR LOADING CONDITIONS NOT SHOWN IN THESE DETAILS ARE NOT PART OF THIS APPROVAL.


MATERIALS INCLUDING BUT NOT LIMITED TO STEEL/METAL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF THE FLORIDA BLDG. CODE SECTION 2003.8.4.

INSTRUCTIONS:

USE CHARTS AS FOLLOWS.

- STEP 1 DETERMINE DESIGN WIND LOAD REQUIREMENT BASED ON WIND VELOCITY, BLDG. HEIGHT, WIND ZONE USING APPLICABLE ASCE 7 STANDARD.
- STEP 2 SEE CHARTS ON SHEET 2 FOR DESIGN LOAD CAPACITY OF DESIRED GLASS SIZE.
- STEP 3

 CHECK MULLION AND JAMB CAPACITY FOR A GIVEN SPACING AND HEIGHT USING CHARTS ON SHEET 3. THE CAPACITY SHOULD EXCEED THE DESIGN LOAD.
- STEP 4 THE LOWEST VALUE RESULTING FROM STEPS 2 AND 3 SHALL APPLY TO ENTIRE SYSTEM.



PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No
Expiration Date

03 | 15 | 20 | 4

By


Rev. 12 | 14

DAYLITE OPENINGS: D.L.O. HEIGHT = FRAME HEIGHT - 6"

D.L.O. WIDTH = FRAME WIDTH - 6"

Miami Dade Product Control

WINDOW WALL SYSTEM WITH GLASS TYPES 'A', 'A1' & 'B' COMPLY WITH REQUIREMENTS OF ANSI Z97.1.



date: 12–19–03
scale: 1/2"=1'-0'
dr. by: HAMID
chk. by:

sheet 1 of 7

revision no date 6 09.28.0 H 04.21. 1 08.04.

U

AL-FAROOQ CORPORATION ENGINEERS & PRODUCT DEVELOPMENT

HP3070 ALUM. WINDOW WALL SYSTEM (L.M.I.)

R.C. ALUMINUM INDUSTRIES 2805 N.W. 75 TH AVE. MIAMI, FL. 33122 TEL. (305) 592-1515 FAX. (305) 592

S S S

GI	LASS DESIGN I	LOAD CAPAC	ITY - PSF		
27.02.000			GLASS TYPE	1	S TYPE
NOMIN	AL DIMS	'A'	'A1'	<u> </u>	'B'
D.L.O. WIDTH	D.L.O. HEIGHT	EXT. (+) INT. (-)	EXT. (+)	EXT. (+)	INT. (-)
24"		160.0	110.0	74.0	117.0
27"	1	160.0	110.0	74.0	117.0
30"		160.0	110.0	74.0	117.0
33"	1	160.0	110.0	74.0	117.0
36"		160.0	110.0	74.0	117.0
39"		160.0	110.0	74.0	117.0
42"		160.0	110.0	74.0	117.0
45"	1 1	160.0	110.0	74.0	117.0
48"	60"	160.0	110.0	74.0	117.0
51"	j	150.0	110.0	74.0	117.0
54"	j [150.0	110.0	74.0	117.0
57"		150.0	110.0	74.0	117.0
60"	[150.0	110.0	74.0	117.0
63"	[150.0	110.0	74.0	117.0
66"	l [150.0	110.0	74.0	117.0
69"	[150.0	110.0	74.0	117,0
72°		150.0		-	
24"		160.0	110.0	74.0	117.0
27"		160.0	110.0	74.0	117.0
30"		160.0	110.0	74.0	117.0
33"		160.0	110.0	74.0	117.0
36"	_	160.0	110.0	74.0	117.0
39"		160.0	110.0	74.0	117,0
42"	_	160.0	110.0	74.0	117.0
45"		150.0	110.0	74.0	117.0
48"	66"	150.0	110.0	74.0	117.0
51"		150.0	110.0	74.0	117.0
54"	-	150.0	110.0	74.0	117.0
57"		150.0	110.0	74.0	117.0
60"	-	150.0	110.0	74.0	117.0
63"	<u> </u>	150.0	110.0	74.0	117.0
66"	-	150.0		74.0	117.0
69" 72"	-	150.0		74.0	117.0
24"	<u>_</u>	147.0			
27"	-	160.0	110.0	74.0	117.0
30"	-	160.0	110.0	74.0	117.0
33"		160.0	110.0	74.0	117.0
36"	-	160.0	110.0	74.0	117.0
39"	_	160.0	110.0	74.0	117.0
42"	-	160.0	110.0	74.0	117.0
42 45"	<u> </u> -	150.0	110.0	74.0	117.0
45 48"	-	150.0	110.0	74.0	117.0
Í	72"	150.0	110.0	74.0	117.0
51" 54"	<u> </u>	150.0	110.0	74.0	117.0
	<u> </u> -	150.0	110.0	74.0	117.0
57"	ļ	150.0	110.0	74.0	117.0
60" 63"	<u> </u>	150.0		74.0	117.0
66"	<u> </u>	150.0		74.0	117.0
		147.0		74.0	117.0
69"				74.0	117.0

	GLASS DESIGN LOAD CAPACITY - PSF									
		LASS DESIGN								
	NOMINAL DIMS		GLASS TYP	E GLASS TYPI	1	S TYPE 'B'				
	D.L.O. WIDTH	D.L.O. HEIGHT	EXT. (+) INT. (-)	EXT. (+)	EXT. (+)	INT. (-)				
	24"		160.0	110.0	74.0	117.0				
	27"		160.0	110.0	74.0	117.0				
ĺ	30"		160.0	110.0	74.0	117.0				
	33"		160.0	110.0	74.0	117.0				
į	36"	İ	160.0	110.0	74.0	117.0				
	39"		150.0	110.0	74.0	117.0				
1	42"		150.0	110,0	74.0	117.0				
ľ	45"		150.0	110.0	74.0	117.0				
١	48"	78"	150.0	110.0	74,0	117.0				
١	51"		150.0	110.0	74.0	117.0				
ı	54"		150.0	110.0	74.0	117.0				
l	57"		150.0		74.0	117.0				
ĺ	60"		145.0		74.0	117.0				
l	63"		141,0		74.0	117.0				
İ	24"	 	160.0	110.0	74.0	117.0				
l	27"		160.0	110.0	74.0	117.0				
l	30"		160.0	110.0	74.0	117.0				
ĺ	33"		160.0	110.0	74.0	117.0				
ı	36"	}	150.0	110.0	74.0	117.0				
۱	39"		150.0	110.0	74.0	117.0				
ı	42"	84"	150.0	110.0	74.0	117.0				
l	45"		150.0	110.0	74.0	117.0				
l	48"		150.0	110.0	74.0	117.0				
l	51"		150.0	- 110.0	74.0	117.0				
ľ	54"		147,0		74.0	117.0				
l	57"		141.0		74.0	117.0				
l	60"			_	74.0	117.0				
l	63"				74.0	117.0				
r	24"		160.0	110.0	74.0	117.0				
l	27"	ĺ	160.0	110.0	74.0	117.0				
l	30"		160.0	110.0	74.0	117.0				
ı	33"	}	150.0	110.0	74.0	117.0				
l	36"		150.0	110.0	74.0	117.0				
ı	39"	00"	150.0	110.0	74.0	117.0				
ĺ	42"	90"	150.0	110.0	74.0	117.0				
	45"	ľ	150.0	110.0	74.0	117.0				
	48"	 	150.0	_	74.0	117.0				
	51"	ľ	143.0		74.0	117.0				
	54"	1	137.0		74.0	117.0				
	57"		_		74.0	117.0				
	24"		160,0	110.0	74.0	117.0				
	27"	ł	160.0	110.0	74.0	117.0				
	30"	ŀ	160.0	110.0	74.0	117.0				
	33"	-	150.0	110.0	74.0	117.0				
	36"	}	150.0	110.0	74.0	117.0				
	39"	96"	150.0	110.0	74.0	117.0				
	42"	-	150.0	110.0	74.0	117.0				
	45"	}	150.0		74.0					
	48"	}	142.0		74.0	117.0				
	51"	}	135.0			117.0				
	54"	-			74.0	117.0				
_	V-1				74.0	117.0				

	GLASS DESIGN LOAD CAPACITY - PSF								
	NOMIN	AL DIMS	GLASS TYPE 'A'	GLASS TYPE	ļ	TYPE B'			
	D.L.O. WIDTH	D.L.O. WIDTH D.L.O. HEIGHT		EXT. (+) INT. (-)	EXT. (+)	INT. (-)			
	24"		160.0	110.0	74.0	117.0			
	27"		160.0	110.0	74.0	117,0			
	30"		150.0	110.0	74.0	117.0			
	33"		150.0	110.0	74.0	117.0			
	36"		150.0	110.0	74.0	117.0			
i	39"	102"	150.0	110.0	74.0	117.0			
	42"		150.0	_	74.0	117.0			
	45"		143.0	-	74.0	117.0			
	48"		134.0	-	74.0	117.0			
	51"			-	74.0	117.0			
	24"		160.0	110.0	74.0	117.0			
	27"		160.0	110.0	74.0	117.0			
	30"		150.0	110.0	74.0	117.0			
١	33"		150.0	110.0	74.0	117.0			
I	36"	108"	150.0	110.0	74.0	117.0			
Ì	39"		150.0	110.0	74.0	117.0			
I	42"		147.0	-	74.0	117.0			
I	45"		136.0	-	74.0	117.0			
1	48"		-	-	74.0	117.0			
I	24"		160.0	110.0	74.0	117.0			
l	27"		150.0	110.0	74.0	117.0			
١	30"	[150.0	110.0	74.0	117.0			
I	33"	114"	150.0	110.0	74.0	117.0			
1	36"	114	150.0	110.0	74.0	117.0			
١	39"		150.0	-	74.0	117.0			
l	42"		141.0		74.0	117.0			
ŀ	45"			-	74.0	117.0			
١	24"		160.0	110.0	74.0	117.0			
ļ	27"	ļ	150.0	110.0	74.0	117.0			
ĺ	30"	120"	150.0	110.0	74.0	117.0			
l	33"	120	150.0	110.0	74.0	117.0			
l	36"		150.0		74.0	117.0			
I	39"	Į.	150.0		74.0	117.0			
Ĺ	42"		-	-	74.0	117.0			

NOTE: GLASS CAPACITIES ON THIS SHEET ARE BASED ON ASTM E1300-04 (3 SEC. GUSTS).

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 12-0330. 14
Expiration Date 23/15/2014
By flux notation Bade Product Control

Engr: JAVAD AHMAD CIVIL FLA. PE # 70592 C.A.N. 3538


MAR 1 5 2012


U	}			
RPORATION	C DEVELOPMENT			FAX. (305) 262-6978
AL-FAROOQ CORPORATION	ENGINEERS & PRODUCT DEVELOPMENT	1235 S.W. 87 AVE	MIAMI, FLORIDA 33174	TEL. (305) 264-8100


| HP3070 ALUM. WINDOW WALL SYSTEM (L.M.I.) | R.C. ALUMINUM INDUSTRIES INC. 2805 N.W. 75 TH AVE. MIAMI, FL. 33122 | TEL (305) 592-1515 FAX. (305) 592-2184

drawing no. W03-115

sheet 2 of 7







Engr: JAVAD AHMAD CIVIL FLA. PE # 70592 C.A.N. 3538

MAR 1 5 2012

AI -FAROOO CORPORATION		100F C. W. CZ AVE	MIAMI ELODIDA 99474		IEL. (305) 264-8100 FAX. (305) 262-6978	STORE\W03-
HEROTO ALLIM WINDOW WALL SYSTEM (LIMIT) OF LEAROOD CORPORATION		R.C. ALUMINUM INDUSTRIES INC.	2805 N.W. 75 TH AVE	1000 N.W. 70 III OVE.		TEL. (305) 592-1515 FAX. (305) 592-2184
revisions:	no date by description		H 04.21.10 GLASS TYPE 'B' ADDED	1 08.04.10 NO CHANGE THIS SHEET	J 03.08.12 UPDATED TO 2010 FBC	
() date: 12–19–03		scale: 1/2" = 1"		dr. by: MAMID		chk. by:


drawing no. W03-115 sheet 2.1 of 7


FAX. (305) 262-697

	ION/JAMB DE	7	REINF.	7	I REINF.
		JAM	В 'J1'	 	
		JAM	В 'ЈЗ'	JAN	MB 'J2'
NOMINAL DIMS. WIDTH (W) FRAME HEIGHT		MULLI	ON 'M1'	MULL	ion 'm2'
		EXT.(+)	INT.()	EXT.(+)) INT.(-)
30"		150.0	160.0	150.0	160.0
36"		150.0	160.0	150.0	160.0
42"		150.0	160.0	150.0	160.0
45"		150.0	160.0	150.0	160.0
48"	66"	150.0	160.0	150.0	160.0
54"		150.0	160.0	150.0	160.0
60"		150.0	160.0	150.0	160.0
66"		150.0	160.0	150.0	160.0
72"		150.0	160.0	150.0	160.0
30"		150.0	160.0	150.0	160.0
36"		150.0	160.0	150.0	160.0
42"		150.0	160.0	150.0	160.0
45"		150.0	160.0	150.0	160.0
48"	72"	150.0	160.0	150.0	160.0
54"		150.0	160.0	150.0	160.0
60"	[150.0	160.0	150.0	160.0
66"		150.0	160.0	150.0	160.0
72"		150.0	160.0	150.0	160.0
30"		150.0	160.0	150.0	160.0
36"		150.0	160.0	150.0	160.0
42"		150.0	160.0	150.0	160.0
45"		150.0	160.0	150.0	160.0
48"	78"	150.0	160.0	150.0	160.0
54"	<u> </u>	150.0	160.0	150.0	160.0
60"	-	150.0	160.0	150.0	160.0
66"	<u> </u>	150.0	160.0	150.0	160.0
72"			-	100.0	138.0
30" "	_	150.0	160.0	150.0	160.0
36"	-	150.0	160.0	150.0	160.0
42"	-	150.0	160.0	150.0	160.0
45"		150.0	160.0	150.0	160.0
48" 54"	84"	150.0	160.0	150.0	160.0
60"	-	150.0	160.0	150.0	160.0
66"	<u> </u>	150.0	160.0	150.0	160.0
72"	-		150.0	150.0	150.0
30"	·	150.0	160.0	100.0	138.0
36"	-	150.0	160.0	150.0	160.0
42"	-	150.0	160.0	150.0	160.0
45"	-	150.0	160.0	150.0	160.0
48"	⊢	150.0	160.0		160.0
54"	<u></u>	150.0	160.0	150.0 150.0	160.0
60"	H-	150.0	150.0	150.0	160.0
66"			, 50.0	100.0	150.0
72"	-	 +	_ +	90.0	138.0
				90.0	117.0


MULLION/JAMB DESIGN LOAD CAPACITY - PSF W/O REINF. WITH REINE									
				WITH REINF.					
NOMIN	AL DIMS.	JAM.	B 'J1' B 'J3' ON 'M1'		B 'J2' ON 'M2'				
WIDTH (W)	FRAME HEIGHT	EXT.(+)	INT.(~)	EXT.(+)	INT.()				
30"		150.0	160.0	150.0	160.0				
36"		150.0	160.0	150.0	160.0				
42"		150.0	160.0	150.0	160.0				
45"		150.0	160.0	150.0	160.0				
48"	96"	150.0	160.0	150.0	160.0				
54"		150.0	160.0	150.0	160.0				
60"		-		100.0	138.0				
66"		_	-	90.0	117.0				
72"		_	_	90.0	117.0				
30"		150.0	160.0	150.0	160.0				
36"		150.0	160.0	150.0	160.0				
42"		150.0	160.0	150.0	160.0				
45"	100"	150.0	160.0	150.0	160.0				
48"	102"	150.0	160.0	150.0	160.0				
54"		150.0	150.0	150.0	150.0				
60"		_	_	100.0	138.0				
66"		_	_	90.0	117.0				
30"		150.0	160.0	150.0	160.0				
36"		150.0	160.0	150.0	160.0				
42"	•	150.0	160.0	150.0	160.0				
45"	100"	150.0	160.0	150.0	160.0				
48"	108"	150.0	160.0	150.0	160.0				
54"		-		100.0	138.0				
60"		_		90.0	117.0				
30"		150.0	160.0	150.0	160.0				
36"		150.0	160.0	150.0	160.0				
42"		150.0	160.0	150.0	160.0				
45"	114"	150.0	160.0	150.0	160.0				
48"		150.0	150.0	150.0	150.0				
54"		-		90.0	117.0				
60"				90.0	117.0				
30"		150.0	160.0	150.0	160.0				
36"		150.0	160.0	150.0	160.0				
42"	120" -	150.0	160.0	150.0	160.0				
45"	120	150.0	150.0	150.0	150.0				
48"	ſ		- 1	100.0	138.0				
54"		-	-	90.0	117.0				

MULLION/JAMB DESIGN LOAD CAPACITY - PSF										
		W/0	REINF.	WITH REINF.						
NOMIN	AL DIMS.	JAM	B 'J1' B 'J3' DN 'M1'	JAMB 'J2' MULLION 'M2'						
WIDTH (W)	FRAME HEIGHT	EXT.(+)	INT.(-)	EXT.(+)	INT.(-)					
30"				100.0	138.0					
36"			_	100.0	138.0					
42"	100		-	100.0	138.0					
45"	126"	_	-	100.0	138.0					
48"		_	_	100.0	138.0					
54"		_		90.0	117.0					
30"		_		100.0	138.0					
36"	132"		_	100.0	138.0					
42"		-	-	100.0	138.0					
45"		_	-	100.0	138.0					
48"		_	-	90.0	110.0					
30"		-	_	100.0	138.0					
36"		-	-	100.0	138.0					
42"	138"			100.0	138.0					
45"		_	_	90.0	110.0					
48"		-	-	90.0	110.0					
30"	'			100.0	138.0					
36"				100.0	138.0					
42"	144"			100.0	138.0					
45"		-		90.0	110.0					
48"		-	-	90.0	110.0					
30"		-		90.0	110.0					
36"	[-		90.0	110.0					
42"	147-1/2"		-	90.0	110.0					
45"	[.	-		90.0	110.0					
47-1/2"				90.0	110.0					





WIDTH (W) = W1AT FRAME JAMB



W1 + W2 WIDTH(W) =AT FRAME MULLION

JAMB 'J1'

J1 ALUM Ix IN^4 19.9014 Sx IN^3 5.5626

<u>JAMB 'J3'</u>

J3 ALUM Ix IN^4 22.7838 Sx IN^3 6.4247

M1 ALUM Ix IN^4 21.4964 Sx IN^3 6.0405

MULLION 'M1'

JAMB 'J2'

MULLION 'M2'

 J2/M2
 ALUM
 STEEL

 Ix IN^4
 21.4964
 5.2083

 Sx IN^3
 6.0498
 2.0833

PRODUCT REVISED as complying with the Florida
Building Code |2-0330. |4
Acceptance No |23/75/20/4


By Leuc in Miami Dade Product Control


Engr: JAVAD AHMAD CIVIL FLA. PE # 70592 C.A.N. 3538


MAR 1 5 2012


)	1
AL-FAROOQ CORPORATION	ENGINEERS & PRODUCT DEVELOPMENT 1235 S.W. 87 AVE	TEL (305) 264-8100 FAX. (305) 262-6978	STORE\W03-1
HP3070 ALUM. WINDOW WALL SYSTEM (L.M.I.) AL-FAROOQ CORPORATION	R.C. ALUMINUM INDUSTRIES INC.	MIAMI, FL. 33122	TEL. (305) 592-1515 FAX. (305) 592-2184
revisions:	G 09.28.09 REV. PER BCCO COMMENTS H 04.21.10 CHART REV.	1 08.04.10 NO CHANGE THIS SHEET J 03.08.12 NO CHANGE THIS SHEET	
	ıwing	no	. JU[clik. by.
WC	۱٦ ۱	115	: 11

(sheet 3 of 7)









MATERIALS LIST								
ITEM NO. PART NUMBER QUANTITY		QUANTITY	DESCRIPTION	MATERIAL	MANF./SUPPLIER/REMARKS			
1	HP3060-051	AS REQD.	FRAME HEAD/SILL	6005-T6	2-4			
2	FX345-006	AS REQD.	GLAZING RETAINER (HEAD/SILL)	6063-T6				
3	FX345-005	AS REQD.	GLAZING RETAINER (HORIZONTAL)	6063-T6	-			
4	HP3060-044	AS REQD.	FRAME JAMB	6063-T6	-			
4A	HP3060-066	AS REQD.	CLOSED FRAME JAMB	6005-T6	-			
5	HP3060-041	AS REQD.	HORIZONTAL	6063-T6	-			
6	HP3060-042	AS REQD.	FEMALE MULLION	6063-T6	-			
7	HP3060-043	AS REQD.	MALE MULLION	6063-T6	-			
8	HP3060-011	AS REQD.	SNAP-IN COVER HEAD/SILL	6063-T6	_			
9	WV-3289	AS REQD.	BULB GASKET	VINYL	WIBORG			
10	V-088	AS REQD.	OFFSET GASKET	VINYL	-			
11	-	2/ LITE	SETTING BLOCKS (3/4" X 5/8" X 3-1/4")	NEOPRENE	LOWE			
11A	_	2/ LITE	SETTING BLOCKS (1/2" X 1/4" X 4")	NEOPRENE	LOWE			
12	_	-	SEALANT DOW CORNING 995	SILICONE	-			
13	_	_	SEALANT DOW CORNING 795	SILICONE	-			
14	A-36	AS REQD.	REINFORCING BAR (1/2" X 5"), FULL LENGTH	STEEL	SILICONED IN PLACE			
15	; -	AS REQD.	FRAME ASSEMBLY SCREWS	-	# 12 X 1-1/4" PH SMS			
16		AS REQD.	LEVELING SCREWS	-	1/4-20 X 3/4" HH MS			
17		AS REQD.	ANCHOR TUBE (2 X 3 X 1/8")	-	7-3/4" LONG			
18		AS REQD.	FILLER TUBE	6063-T5	-			
19 - AS REQD.		AS REQD.	3/16" X 1/2" NORTON SINGLE FACE TAPE	-	V2100 SERIES			

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 12-0330.14
Expiration Date 03/15/2014

Miami Bade Product Control

Engr: JAVAD AHMAD
CIVIL
FLA. PE # 70592
C.A.N. 3538

MAR 1 5 2012

	_				2	씱
CORPORATION		ACOL CAN GO AVE	777		FAX. (305) 262-6978	STORE\W03-
A! -FAROOO		ACOUNT ON OU AVE	MIAMI EL OBIDA 33174	TI COST DOT OFF	IEL (305) 264-8100	
HE3070 ALLIM WINDOW WALL SYSTEM (LM.) THE PAROOD CORPORATION		R.C. ALUMINUM INDUSTRIES INC.	2805 N W 75 TH AVE	MIANI	MIAMI, FL. 33122	UTEL. (305) 592-1515 FAX. (305) 592-2184
ns:	e by description	.09 REV. PER BCCO COMMENTS	.10 GLASS TYPE 'B' ADDED	.10 NO CHANGE THIS SHEET	3.08.12 NO CHANGE THIS SHEET	
3 ∩ revisio	100 B	G 09.28.09	Н 04.2	1 08.04.10	- 33.00 10.00	

drawing no.

W03-115